ViewSonic®

PJ501 Projector

Ultra-Portable SVGA Projector

- **1,500 lumens in only 2,5 kg.**
  Step up to super-bright images.
- **Native SVGA resolution**
  Native SVGA (800x600) resolution for clear, crisp images.
- **Whisper-mode operations**
  Whisper-mode for extended lamp life and low noise output.
- **Displays HDTV signals**
  Including 480i, 480p, 575i, 720p and 1080i.
- **Easy set-up and auto tuning**
  One-touch setup button for fast, easy sync and sharp focus.
- **User-replaceable extended-life lamp**
  Extended lamp life up to 4,000 hours.*
- **Supports 4:3 and 16:9 aspect ratios**
  Offering increased flexibility for multiple formats.
- **Three-year limited warranty**

Step up to a bright, ultra-portable, quiet projector.

Ideal for mobile professionals, the ViewSonic PJ501 projector offers high brightness at 1,500 lumens in a lightweight 2,5 kg package.You'll present a better image with native SVGA resolution compressing to XGA resolution. Aspect ratios of 4:3 and 16:9, a short focal length, and zoom function add the versatility you need for all your presentations. Plus, the component video feature for superior video quality and whisper-mode setting for long lamp life make the ViewSonic PJ501 projector the dependable choice for the mobile presenter in the office and on the road.

ViewSonic®

www.ViewSonicEurope.com

ViewSonic®

PJ501 Projector

- **Digital keystone correction**
  Squares up the picture even when projecting at an angle.

- **Soft carry case**
  Soft carry case included for easy travel.
  Optional rugged hard case is also available.

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ULTRA-PORTABLE SVGA PROJECTOR

LCD	**Type**	3-panel 0.7" TFT active matrix LCD
	Resolution	SVGA 800x600, compressed to 1024x768
	Pixel Format	800 Horizontal x 600 Vertical
	Lens	Manual zoom/focus (manual x 1.2)
DISPLAY	**Size**	30"–300" (measured diagonally)
	Throw Distance	0.7m–9m (2.3'–29.5')
	Lamp	150W UHB Compact, 4,000[2] hour rating
	Brightness	1,500 Lumens
	Contrast Ratio	400:1
	Keystone Correction	±10 degrees
	Aspect Ratio	4:3, 16:9
AUDIO	**Speaker**	1W monospeaker
INPUT SIGNAL	**Video**	RGB analog, NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, 480i, 480p, 575i, 720p, 1080i
	Sync	Separated and Composite
	Frequency	F_h: 15~78kHz; F_v: 56~120Hz
COMPATIBILITY	**PC**	From VGA up to XGA
	Mac®	Up to XGA (may require Mac Adapter)
CONNECTOR	**RGB Input**	15-pin HD, D-sub (x1)
	Composite Video	RCA (x1)
	S-Video	Mini-Din 4 pin (x1)
	Component	RCA (x3)
	Audio In	RCA (x1)
	Audio Out	3.5mm stereo mini jack (optional)
	Control	15-pin D-sub (RS232 optional)
POWER	**Voltage**	100–120V AC / 220–240V AC, 50–60Hz (universal)
	Consumption	210W (typ), 130W (whisper-mode)
USER CONTROLS	**Basic**	Standby on/off, menu (left, right, up, down), input, reset, mute, indicator (lamp, power, temp)
	Remote	Standby on/off, video, RGB, menu, keystone, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer, auto, blank
	OnView ®	Brightness, contrast, V. position, H. position, H. phase, H. size, colour balance (red), colour balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu colour, timer, language, auto off, sync on green
OPERATING CONDITIONS	**Temperature**	0° C–35° C (32° F–95° F)
	Humidity	10%–85% (non-condensing)
DIMENSIONS	**Physical**	277mm (W) x 211mm (D) x 61mm (H) (10.9" x 8.3" x 2.4")
WEIGHT	**Net**	2.50 kg (5.4 lbs.)
REGULATIONS		UL, FCC-B, c-UL, CE, TUV/GS, CB Report, PCT
OTHER		Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic®

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (9) 54 06 40 70
ViewSonic Italy Tel: +39 0289 079 340
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] The warranty for all ViewSonic LCD and DLP projectors (except PJ250) from 1 April 2004 is valid for three years, and includes an on-site exchange service during this period in all current European Union (France, Belgium, Netherlands, Luxembourg, United Kingdom, Ireland, Sweden, Denmark, Finland, Germany, Austria, Greece, Italy, Spain, Portugal) and EFTA countries (Switzerland, Liechtenstein, Norway, Iceland). [2] Running eco-mode extends life beyond 2,000 hours if proper care of lamp is taken. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. Copyright © 2004 ViewSonic Corporation. All rights reserved.
PJ501-2-6/04-UK